

TripMate852

Overview

TripMate852 features all-in-one, cost-effective portable GPS logger solution. When you travel in different countries, it allows you to record your routes by ways of time/ distance/ speed. TripMate852 includes LED indicators for real time status display. Through user friendly utility software, it can combine your pictures and record routes showing on the map. This recorder is small and robust, ideal to carry everywhere for applications such as route tracking, mountain climbing or fleet management.

Key Features

- ⊙ MTK 3329 chip with 66 channel capability
- ⊙ Smart log function
- ⊙ Receiver & data logger dual function design
- ⊙ Smart power saving with sensor
- ⊙ Micro SD card for POI storage
- ⊙ LED display
- ⊙ Support AGPS
- ⊙ Powered by AAA battery*2



Application

- ⊙ Record your travels and show on Google Earth
- ⊙ Show your photos on Google Map
- ⊙ Support photo Geo Tagging



TripMate852

Specifications

General

Frequency	L1, 1575.42MHz
C/A Code	1.023MHz chip rate
Channels	66 CH for tracking
Datum	WGS-84

Acquisition

Cold Start	35 sec, average
Warm Start	34 sec, average
Hot Start	1.5 sec, average
AGPS	<15 sec

Accuracy (none DGPS)

Position	Without aid: 3.0m 2D-RMS DGPS:2.5m,2D-RMS
Velocity	Without aid: 0.1m/s DGPS:0.05m/s
Sensitivity	-165 dBm (tracking)

Dynamic

Altitude	< 18,000m
Velocity	< 515m/sec
Acceleration	4g

Protocol

GPS Output	NMEA-0183 (V3.01) – GGA, GSA, GSV, RMC
	Data bit : 8, stop bit : 1(Default)

Interface

SD	Micro SD card (up to 8G)
USB Bridge	Fully compliant with USB2.0, 12Mbps

Power

Battery	AAA battery*2
Operation Time	Up to 12hrs [☆]
Power On/Off	Push button

☆ : Pending battery type

Environmental

Operating	- 10 °C to + 60 °C
Storage	- 20 °C to + 60 °C
Charging	0 °C to + 45 °C
Humidity	5% to 90% non-condensing

Physical

Dimension	72 x 27 x 25mm
Weight	57.5g (with battery)

Others

5Hz	Push button
Certification	CE / FCC

* Specifications subject to change without prior notice.

* Copyright ©2009 G&V Global Tech Co., Ltd. all rights reserved.

* Citation MTK chipset specifications.



9Fl., No 6, Lane 77, Section 2 HuanShan Rd., NeiHu District, Taipei City, Taiwan

Tel: 02-8751-9952

Fax: 02-8751-2663

www.gvglobaltech.com

Rev 1.5