mobileMate 886

Miniature GPS Receiver

Overview

At just 44mm in length, the featured mobile Mate 886 is one of the world's smallest models. Equipped with a 66-channel MTK chipset, it provides ultra-high sensitivity -165dBm tracking and -148dBm signal acquisition. And by coupling smart power-saving options with fuzzy auto on/off, it's also the most power-efficient receiver available. Ultra-short in length, highly sensitive and super-efficient, this device enjoys wide consumer appeal.

Key Features

- 66 channels Bluetooth GPS
- Supports G-mouse function
- Ultra high sensitivity up to -165 dBm (Tracking)
- Smart Power Save Mechanism
- Fuzzy Auto On/Off
- Support AGPS

Application

- Automotive
- Fleet management / Asset tracking
- Personal / portable Navigation (PDA, Smart phone)
- Location Based Services
- Sports and Recreation
- Geographic Survey



9Fl., No 6, Lane 77, Section 2 HuanShan Rd., NeiHu District, Taipei City, Taiwan Tel: 02-8751-9952 Fax: 02-8751-2663

mobileMate 886

Miniature GPS Receiver

Specifications

| General | |
|-----------|-------------------------|
| Frequency | L1, 1575.42MHz |
| C/A Code | 1.023MHz chip rate |
| Channels | 66 CH for tracking |
| Antenna | Built-in patch with LNA |
| Datum | WGS-84 |

| Acquisition | |
|-------------|------------------|
| Cold Start | 35 sec, average |
| Warm Start | 34 sec, average |
| Hot Start | 1.5 sec, average |
| AGPS | <15 sec |

Accuracy (none DGPS) Position Without aid: 3.0m 2D-RMS DGPS:2.5m,2D-RMS Without aid: 0.1m/s DGPS:0.05m/s Sensitivity -165 dBm (tracking)

| Dynamic | |
|--------------|------------|
| Altitude | < 18,000m |
| Velocity | < 515m/sec |
| Acceleration | 4g |

| Protocol | |
|---------------|---|
| GPS Output | NMEA-0183 (V3.01) – GGA, GSA, GSV, RMC |
| | Data bit : 8, stop bit : 1(Default) |

| Interface | |
|-------------------------|---------------------------|
| Bluetooth TM | Version 1.2 compliant |
| Output Power | Class 2 (over 10 meter in |
| | free space) |
| Frequency | 2.4 to 2.48 GHz |

| Power | |
|----------------|----------------------|
| Battery | Rechargeable battery |
| Operation Time | 11hrs |
| Power On/Off | Push button |
| Power Charge | Mini USB |

| Environmental | |
|---------------|---|
| Operating | - $10 ^{\circ}\text{C}$ to + $60 ^{\circ}\text{C}$ |
| Storage | - 20 °C to + 60 °C |
| Charging | $0 ^{\circ}\!\!\text{C}$ to + 45 $^{\circ}\!\!\text{C}$ |
| Humidity | 5% to 90% non-condensing |
| Humidity | 5% to 90% non-condensing |

| Physical | |
|-----------|----------------|
| Dimension | 44 x 26 x 15mm |
| Weight | 18g |

| Others | |
|---------------|---------------------------|
| BT/ Cable | Supports G-mouse function |
| Certification | CE / FCC |
| LED | Bluetooth, Navigation, |
| | Battery / charger status |

^{*}Bluetooth is a trademark owned by Bluetooth SIG, Inc. *Specifications subject to change without prior notice. Copy right ©2009 G&V Global Tech Co., Ltd. all rights reserved.

